

H



HOBNAIL

from our
FIBRE BONDED RANGE





HOBNAIL

 **MADE IN THE UK. MADE TO LAST.**

Specification

PRODUCT	Hobnail Heavy Contract Carpet and Tiles
FIBRE CONSTRUCTION	80% Polypropylene, 15% Polyamide, 5% Recycled Polyester
WEIGHT	1020gm metre ² (Sheet), 4020gm metre ² (Tile)
THICKNESS	7.2mm (Sheet), 8.0mm (Tile)
ROLL WIDTH	 2 metre
TILE SIZE	 50cm x 50cm (Tiles are Bitumen backed)
COLOUR FASTNESS	Light (BS EN ISO 105:802) >6 Wet Rubbing (BS EN ISO 105:B01) 5 Dry Rubbing (BS EN ISO 105:X12) 5
FLAMMABILITY	(BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char
BS EN 13501	Euroclass C _{fl} -s1 (Sheet) Euroclass B _{fl} -s1 (Tile)
ANTISTATIC	Suitable for use in computer rooms
INSTALLATION	 The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit: www.heckmondwike-fb.co.uk . Before laying Hobnail, tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels. Hobnail tiles should be laid rotationally, alternating the direction of the tiles through 90°.
ADHESIVE GUIDE	Sheet carpet should be fully adhered with F Ball's F3 or Bostik Laybond Carpet Adhesive. Sheet carpets can be laid into F40 as a release system. For tiles, use Tackifier F41 or Bostik Laybond Carpet tile Tackifier.
MAINTENANCE	To achieve maximum life expectancy, it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.

CE EN 14041 Heckmondwike FB Liversedge WF15 7FH 09 Hobnail Sheet Fibre Bonded Sheet Floorcovering intended for internal use	CE EN 14041 Heckmondwike FB Liversedge WF15 7FH 09 Hobnail Tile Fibre Bonded Tile Floorcovering intended for internal use
 C _{fl} -s1	 B _{fl} -s1
 NPD	 NPD



BCFA
member