



S STICKS & STONES

ENTRANCE & TRANSITION AREA RANGE

 **MADE IN THE UK. MADE TO LAST.**

Specification

PRODUCT	Sticks & Stones Heavy Contract Fibre Bonded Tiles
FIBRE CONSTRUCTION	85% Polypropylene, 15% Recycled Polyester
WEIGHT	4625gsm
THICKNESS	13mm
TILE SIZE	 50cm x 50cm (Tiles are Bitumen backed)
TILES PER BOX	16 (4m ²)
COLOUR FASTNESS	Light (BS EN ISO 105:B02) 6 Wet Rubbing (BS EN ISO 105:BO1) 5 Dry Rubbing (BS EN ISO 105:X12) 5
FLAMMABILITY	(BS6307) Methenamine Pill Test - Pass
BS EN 13501	Class Efl
INSTALLATION	 Tiles Sticks & Stones tiles should be laid tessellated as per the icon provided. The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit: www.heckmondwike-fb.co.uk . Before laying Sticks & Stones, tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
ADHESIVE GUIDE	F.Ball F41 or Bostik Laybond Carpet Tile Tackifier
MAINTENANCE	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.



07/21