DESSO Textile floor covering - Tiles

Arable EcoBase™

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/10 “						
Aspect	ISO 2424		Structured loop pile						
Dye method			Solution dyed						
Dimension	EN ISO 24342	cm x cm	50 x 50 / 19,68” x 19,68” (20 tiles per box)						
Primary backing	ISO 2424		Polyester fleece						
Secondary backing	ISO 2424		DESSO EcoBase® * - Containing on average 80% C2C positively defined recycled content.						
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) **						
Total thickness	ISO 1765	mm	6.5	inch	0.3				
Effective pile thickness	ISO 1766	mm	3.2	inch	0.13				
Total mass	ISO 8543	g/m²	4100	oz/yd²	121.0				
Total pile mass	ISO 2424	g/m²	675	oz/yd²	19.9				
Effective pile mass	ISO 8543	g/m²	415	oz/yd²	12.2				
Pile density	ISO 8543	g/cm³	0.130	lb/in³	0.0047				
Number of tufts	ISO 1763	/dm²	1580	/yd²	132104				
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10^9						
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		33 Commercial - heavy use						
Luxury rating	EN 1307		LC 2						
Dimensional stability	EN 986	%	≤ 0,2						
Impact sound reduction ΔL_W	ISO 10140	dB	25						
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000	
		α_s	0.00	0.04	0.07	0.16	0.31	0.37	
Noise reduction	ISO 354	α_w	0.15						
Thermal resistance	ISO 8302	m².K/W	0.071						
Flammability	EN 13501-1		Bfl - s1 (loose laid tested)						
Prodis - GUT	www.pro-dis.info		A4BA8229						

CE
EN 14041
0493-CPR-0002

Manufactured by:
Tarkett BV
Taxandriaweg 15
NL - 5142 PA Waalwijk

Bfl-s1 DS

ECONYL® ENDLESS POSSIBILITIES

Quality- and Environmental Management System Certification ISO 9001 & ISO 14001

* DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® Certified CM Product Standard Version 3.0. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com
** ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

Tarkett’s flooring products are to be installed in full accordance with DESSO installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. Tarkett’s flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20200401

Tarkett BV
Taxandriaweg 15
NL-5142 PA Waalwijk

Tarkett