

technical specifications

Product Description	Carbon Neutral Multilevel Loop
Yarn	Universal Fibers [®] Thrive [®] matter carbon negative recycled yarn
Tile Dimensions	50cm x 50cm
Pile Yarn Weight	635g/m ²
Total Weight	4032g/m ²
Total Thickness	7mm
Construction	1/12th gauge - Multilevel loop pile
Tufts per m2 / Pile Density	226,771/m ²
Backing Description	BioBase[®] recycled backing (recycled BS EN ISO 14021)
Wear Classification	Class 33 heavy commercial use (BS EN 1307)
Luxury Rating Class	LC1
Flammability	Euroclass Bfl-s1
Thermal Resistance	Tog Rating: 0.59
Castor Chair Rating	Pass - continuous use (BS EN 985)
Hexapod	BS ISO 10361: Method B:2000 3 to 4
Static Loading	BS 4939: 1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum Grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4-5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN ISO 10140-3:2010 24dB
Reduction in Impact Noise at 1000Hz	BS EN ISO 10140-3:2010 42.5dB
Number Of Tiles Per Box	20 (5m ²)
VOC	Class A+
Warranty	15 years



eco₂matters[®]

We are committed to helping deliver a sustainable future, because we believe that what we do **matters**. To help us deliver on this commitment, we have developed **eco₂matters[®]**, our sustainability principles, supported by independent 3rd party verification.



rocklines[®] is inspired by the markings seen in rockfaces, mountains and various terrains. An opulent and delicate design, **rocklines[®]** is available in 16 colours, influenced by weathered coastlines and geological diversities. Discover different combinations within the palette of bold, neutral and mixed tones. **rocklines[®]** is **carbon neutral**.




rocklines[®] is **carbon neutral**



Burmatex[®] **reco₂very** take back service provides a no landfill solution for your used tiles



rocklines[®] uses Universal Fibers[®] Thrive[®] matter yarn which is C2C Certified Material Health Certificate™ Silver



Burmatex[®] products are made using 100% certified **renewable** electricity



rocklines[®] uses **BioBase[®] recycled** backing



eco₂matters[®] declarations are independently 3rd party verified

EPD
Burmatex[®] products are supported by 3rd party independently verified, product specific EPD's

LEED
Burmatex[®] products contribute towards Leed accreditation

SKA
Burmatex[®] products adhere to SKA standards

WELL Building Standards
Burmatex[®] products contribute to WELL Building Standards

Contact Us
T +44 (0) 1924 262 525
email: sales@burmatex.co.uk

Burmatex Ltd
Victoria Mills, The Green
Ossett, West Yorkshire
WF5 0AN, United Kingdom

This shade card is the property of Burmatex[®]
Made from **eco laminate** and **100% recyclable card**

Burmatex[®] reserves the right to improve the specification of all products without prior notification. E&OE Burmatex[®] carpets, carpet tiles and carpet planks should be installed and used in full accordance with instructions at www.burmatex.co.uk and recognised trade standards. Orders are subject to Burmatex[®] terms and conditions of sale. See: www.burmatex.co.uk

LRV values

Product code	Product colour name	CIE Y
36101	marble	21.40
36102	causeway	15.01
36103	mountain	10.17
36104	imprint	5.13
36105	climate	22.88
36106	tectonic	22.32
36107	fragment	21.09
36108	terrain	12.15
36109	sunlit	29.02
36110	habitat	24.86
36111	uplift	26.40
36112	burnish	19.76
36113	amethyst	21.50
36114	oceanic	21.20
36115	riptide	9.39
36116	serpentine	10.08