



Installation Method



Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product HN830 **Colour** Cobalt **Collection** Human Nature Collection **Backing** CQuest™Bio

Product Specifications

Product Construction	Tufted Plain Shag Cut Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
Size	25cm x 1m
Tiles per Box	10 - 2.5m ²

More Product Specifications

Pile Yarn Weight	1,425 g/m ² ± 5%
Total Weight	4,674 g/m ² ± 5%
Pile Height	8.2 mm +15% / - 10%
Total Thickness	11.6 mm ±0.5mm
Gauge - Ends per 10 cm	5/32 - 25.2
Tufts per m ²	93240 /m ² ±5%

Performance Specifications

Wear Classification	EN 1307 32 General Contract
Castor Chair Rating	≥2.0 (EN 985) Occasional Use
Flammability	(EN ISO 9239-1: 2010) Euroclass Cfl-s1 (EN 13501-1) Bfl-s1 on request
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	22.20
Light Reflectance Value (LRV-Y)	3.60
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound Insulation ΔLw EN ISO 10140-3	30 dB
Rating of Sound Absorption (αw) EN ISO 11654	0.2
Sound Absorption (αs)EN ISO 354 at 125 Hz	0.02
Sound Absorption (αs)EN ISO 354 at 250 Hz	0.06
Sound Absorption (αs)EN ISO 354 at 500 Hz	0.11
Sound Absorption (αs)EN ISO 354 at 1000 Hz	0.27
Sound Absorption (αs)EN ISO 354 at 2000 Hz	0.41
Sound Absorption (αs)EN ISO 354 at 4000 Hz	0.51

Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	Health Product Declaration
Total Recycled Content	84.6 %
Pre-Consumer (Total)	69.40 %
Post-Consumer (Total)	15.20 %
Yarn Recycled Content	100.00 %
Pre-Consumer (Yarn)	50.00 %
Post-Consumer (Yarn)	50.00 %
Total Bio Based Content	8.11 %
Total Recycled & Bio Based Content	92.71 %
Indoor Air Quality	Compliant with LEED EQ 5.0 credit French A+ M1 Emission Certification -CQB GLP 100209
HQE (France)	View Potential HQE Contribution
DGNB (Germany)	View Potential DGNB Contribution
Embodied Carbon (Cradle to Gate)	3.97 kg CO ₂ eq./m ²
Environmental Certifications	Cradle to Cradle Certified® v3.1 Silver
Installation Waste	Ashlar – 3-5 %
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

Technical Information

Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	10 years
Installation Method	Ashlar
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

Certifications

	 DOP: 1037/127036 EN 14041:2004 Notified Body - 0493 COC 0493 – CFR – 0182 For use as floor covering in buildings	 DOP: 1037/127036 EN 14041:2004 Approved Body - 8515 COC 8515/CFR/0182 For use as floor covering in buildings			
 >0,30	 < 2,0 kV	 30 dB	 0.2	 ≥ 7	
 0.108	 ≥2.0		 ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ B+ C+	 A+ A+ B+ C+	