


technical specifications

Product Name	Rainfall
Product Description	Multilevel Loop
Pile Yarn Description	100% Solution Dyed Aquafil Econyl® Nylon (Polyamide-PA)
Tile Dimensions	50 cm x 50 cm
Pile Yarn Weight	910g/m ²
Total Weight	4300g/m ²
Pile Height	5.0mm
Total Thickness	7.5mm
Gauge/ends per 10cm	1/12th gauge 48 stitches
Tufts per m ² / Pile Density	236,220 /m ²
Backing Description	Accummen™, 75% recycled
Wear Classification	BS EN 1307 Heavy Commercial Use Class 33
Luxury Rating Class	LC3
Flammability	Euroclass Bfl-s1
Thermal Resistance	Tog Rating 0.54; ISO 8302:1991 0.07m ² K/W
Castor Chair Rating	BS EN 985 Pass - suitable for continuous use
Hexapod	BS ISO 10361: Method B:2000 3 to 4
Static Loading	BS 4939: 1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum Grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4-5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN ISO 10140-3:2010 24dB
Reduction in Impact Noise at 1000Hz	BS EN ISO 10140-3:2010 41.6dB
Number Of Tiles Per Box	20 (5m ²)

For best results we recommend



Monolithic



This floor covering was made with renewable electricity



Certificate Number FM01440
BS EN ISO 9001:2015



Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A+ (very low-emission) to C (high-emission)



The Building Information Foundation, Finland. Certified building materials with low emission class M1



Environmental Product Declaration by independent third-party verification of the declaration and data, according to ISO 14025:2006

environmental information

- burmatex® products are EPD verified by an independent third-party verification of the declaration and data, according to ISO 14025:2006. For specific ratings, please refer to www.environdec.com
- burmatex® products qualify for SKA as they achieve one or more requested criteria
- burmatex® products can contribute to the WELL Building Standard™, which focuses on the people and healthy workspaces
- All burmatex® carpet/carpet tile/carpet plank ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of burmatex® Accummen™ backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- All burmatex® products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRC2/MRC3 (Building product disclosure and optimization - environmental product declarations), MRC3/MRC4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd
Victoria Mills, The Green
Ossett, West Yorkshire
WF5 OAN
United Kingdom

T +44 (0) 1924 262 525
F +44 (0) 1924 280 033
UK email: projects@burmatex.co.uk
International email: international@burmatex.co.uk
www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE
Burmatex carpets, carpet tiles and carpet planks should be installed and used in full accordance with instructions at www.burmatex.co.uk and recognised trade standards. Orders are subject to Burmatex terms and conditions of sale. See: www.burmatex.co.uk

LRV values for **rainfall**

Product code tiles	Product colour name	CIE Y	CIE L
22901	light	11.76	40.83
22902	shade	5.40	27.84
22903	dark	3.34	21.37
22904	deep	3.34	21.37
22905	stone	15.16	45.85
22906	pave	5.58	28.32
22907	ground	3.70	22.66
22908	brick	3.31	21.24
22909	birch	13.21	43.07
22910	air	7.45	32.81
22911	bloom	5.14	27.14
22912	leaf	7.95	33.87